



Measuring systems cables for very dynamic applications. MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

For very dynamic applications; PUR Jacket, shielded, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free

CONTACT

Market information
industryprojects.business@lynx
ogroup.com



Halogen free
Yes



Operating temp.
-15 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
EN 50363-10-2

CHARACTERISTICS

Construction characteristics

Construction type	(1x(4x0,14)+4x0,34)C
Conductor material	Tinned copper
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Screen	Tinned copper braid coverage > 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

Dimensional characteristics

Copper content	35 kg/km
Approximate weight	72 kg/km
Outer Diameter	7.3 mm

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	1500 V


Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	EN 50363-10-2

PRODUCT LIST

Reference	Country Ref.	Name
 49498270	-	MEASURING SYSTEM CABLES HEIDNEHAIN® (1x(4x0,14)+4x0,34)C

☎ = Make to order,  = In stock,