



## CONTACT

Market information  
industryprojects.business@lynx  
ogroup.com

**Torsion resistant low-voltage cable for free hanging of max. 100 m**

## STANDARDS

**Product** EN 50363; HD 22-13; IEC 60228; IEC 60502

## APPLICATIONS

Low-voltage loop cable WINDLINK LV-RS (N)HXCSLOE was developed for special application condition in wind turbines. The construction is torsion resistant by free hanging of max.100 m. These cables are specified for medium mechanical stress and for operation under permanent influence of sea water and usage outdoor.

Resistance to

- permanent movement
- permanent vibrations
- compressive stress
- oil, EN60811-2-1, ASTM No.2, 24 h at 100 °C
- low smoke, IEC 61034, >50 %
- halogen-free IEC 60754
- permanent influence of seawater
- ozone influence, EN 60811-2-1 clause 8
- suitable for torsion of max. 6 counterclockwise rotations and min. free hanging up from 25 m

## Design

### Core

### Conductor

- Copper, plain, flexible concentrically stranded circular

### Insulation

- Extruded halogen-free rubber compound EI8 acc. to EN 50363-5

### Screen

- Tinned wire copper braid, covering min. 80 %

### Outer Sheath

- Extruded halogen-free EVA compound EM8 acc. to EN 50363-6

## CHARACTERISTICS

### Caratteristiche costruttive

Senza alogeno	IEC 60754-2
---------------	-------------

### Caratteristiche elettriche

Tensione nominale U <sub>o</sub> /U (Um)	0,6/1 kV
--	----------

### Caratteristiche d'utilizzo

Ritardante la fiamma	EN 50265-2-1
Privo di silicone	Si
Conforme RoHS (2002/95/CE)	Si
Temperatura massima di servizio del conduttore	90 °C
Resistenza alle intemperie	Eccellente
Temperatura massima di cortocircuito del conduttore	250 °C

## PRODUCT LIST

Reference	Country Ref.	Name
☎ 71320700	-	(N)HXCSLOE-JZ 4x1,5
☎ 71320701	-	(N)HXCSLOE-JZ 4x4
☎ 71320702	-	(N)HXCSLOE-JZ 12x1,5
☎ 71320703	-	(N)HXCSLOE-JZ 25x1
☎ 71320704	-	(N)HXCSLOE-JZ 32x1,5
☎ 713207..	-	(N)HXCSLOE-JZ 42x1,5
☎ 71320708	-	(N)HXCSLOE-JZ 12x2,5
☎ 71320706	-	(N)HXCSLOE-JZ 25x0,75
☎ 71320707	-	(N)HXCSLOE-JZ 5x2,5
☎	71320714	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV
☎	-	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV
☎ 71320728	-	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV
☎	71320717	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV

☎ = Make to order, ☎ = In stock,

## SELLING AND DELIVERY INFORMATION

Inkjet marking e.g.: WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV | NEXANS I