



CONTACT

Market information
industryprojects.business@lynx^{eo}.com

- Instrumentation cables 170/300 V
- With lead cover (LC)
- Overall Screen (OS)
- **Aliphatic and aromatic hydrocarbons resistant**

STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cables are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use** in industrial applications, in moist areas, where **hydrocarbon and mechanical protection are needed**. The **lead cover brings an enhanced resistance to aromatics hydrocarbons**. They maintain circuit integrity when exposed to fire.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Silicone rubber (Sil)

Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

Inner sheath:

Low Smoke Zero Halogen (LSZH)

Colour: black

Lead sheath

Bedding (intermediate sheath):

Polyvinyl chloride (PVC)

Colour: black

Armour:

Galvanized steel wires (SWA)

Outer sheath:



Rated Voltage U_o/U_i
(Um)
170/300V



Mechanical
resistance to
impacts
Good



Fire
resistance
IEC 60331



Polyvinyl chloride (PVC)
Colour: black
Other colour on request.
Fire resistance
EN IEC 60332-3-22
(cat A)



Chemical
resistance
**Aliphatic and
aromatic
hydrocarbons
resistant**



Electro magnetic
interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor
temp. in service
90 °C

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

All white core designs with pair number and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx^{eo} is indicative only and shall not be binding on Lynx^{eo} or be treated as constituting a representation on the part of Lynx^{eo}.

Marking

NEXANS 279 SIL/OA.SCR/LSZH//LC/PVC/SWA/PVC 170/300V Nber of pairs & cross-

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	Silicone rubber
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	Low smoke, zero halogen thermoplastic compound
Lead Sheath	Yes
Intermediate sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

Electrical characteristics

Rated Voltage U ₀ /U (Um)	170/300V
--------------------------------------	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Fire resistant	IEC 60331
Fire retardant	EN IEC 60332-3-22 (cat A)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN

SECTION 0.5MM²

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135199	1	0.9	2.06	6.3	8.1	10.1	11.9	13.5	15.7	595
10135200	2	0.9	2.06	7.2	9	11	12.8	14.4	16.7	665
	5	0.9	2.06	12.5	14.5	16.5	19.0	20.4	23.8	1226
	10	0.9	2.06	16.6	18.8	20.8	23.3	24.0	28.0	1712
10135205	20	0.9	2.06	21.9	24.5	26.5	29.0	29.5	34.4	2526
	30	0.9	2.06	26.3	29.1	31.5	34.7	34.8	40.6	3491



Rated Voltage U₀/U (Um)
170/300V



Mechanical resistance to impacts
Good



Fire resistant
IEC 60331



Fire retardant
EN IEC 60332-3-22 (cat A)



Chemical resistance
Aliphatic and aromatic hydrocarbons resistant



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
90 °C

SECTION 0.75MM²

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135207	1	1.1	2.26	6.7	8.5	10.5	12.3	13.9	16.2	630
10135208	2	1.1	2.26	7.6	9.4	11.4	13.2	14.9	17.3	714
	5	1.1	2.26	13.5	15.7	17.7	20.2	21.5	25.0	1389
	10	1.1	2.26	18	20.4	22.4	24.9	25.5	29.7	1968
10135213	20	1.1	2.26	23.7	26.3	28.7	31.9	32.1	37.5	2992
	30	1.1	2.26	29	32	34.4	37.6	37.6	43.9	4057

SECTION 1.0MM²

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135215	1	1.28	2.44	7.1	8.9	10.9	12.7	14.3	16.6	661
10135216	2	1.28	2.44	8	9.8	11.8	13.6	15.3	17.8	753
	5	1.28	2.44	14.4	16.6	18.6	21.1	22.4	26.0	1498
	10	1.28	2.44	19.2	21.6	23.6	26.1	26.7	31.2	2122
10135221	20	1.28	2.44	25.4	28.2	30.6	33.8	34.0	39.7	3409
	30	1.28	2.44	31	34	36.4	39.6	39.4	46.0	4420

SECTION 1.5MM²

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135223	1	1.5	2.66	7.5	9.3	11.3	13.1	14.8	17.2	708
10135224	2	1.5	2.66	8.6	10.4	12.4	14.2	15.8	18.4	815
	5	1.5	2.66	15.5	17.7	19.7	22.2	23.6	27.4	1661
	10	1.5	2.66	20.9	23.5	25.5	28.0	28.4	33.2	2486
10135229	20	1.5	2.66	28	31	33.4	36.6	36.7	42.8	4088
	30	1.5	2.66	33.6	36.8	39.6	43.6	43.2	50.4	5602



Rated Voltage U₀/U
(Um)
170/300V



Mechanical resistance to impacts
Good



Fire resistant
IEC 60331



Fire retardant
EN IEC 60332-3-22
(cat A)



Chemical resistance
Aliphatic and aromatic hydrocarbons resistant



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
90 °C

SECTION 2.5MM²

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
	1	1.91	3.07	8.3	10.1	12.1	13.9	15.5	18.1	784
	2	1.91	3.07	9.5	11.5	13.5	15.3	16.8	19.6	964
	5	1.91	3.07	17.6	20	22	24.5	25.7	29.8	1996
	10	1.91	3.07	23.6	26.2	28.6	31.8	32.0	37.4	3169
	20	1.91	3.07	31.8	35	37.4	40.6	40.5	47.2	4996
	30	1.91	3.07	38.7	42.3	45.1	49.1	48.5	56.6	7190

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U₀/U
(Um)
170/300V



Mechanical resistance to impacts
Good



Fire resistant
IEC 60331



Fire retardant
EN IEC 60332-3-22
(cat A)



Chemical resistance
Aliphatic and aromatic hydrocarbons resistant



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
90 °C