



CONTACT

Markets and Products Information
rollingstock.business@lynxéogroup.com

- Instrumentation cables 150/250(300) V
- CST 74C068
- Zero halogen (SH)
- **Cables installed outside of the containment area (K3)**
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These instrumentation cables allow connection to a variety of measurement equipment. Many of them require anti-inductive screen (EMI).

CONSTRUCTION

Design

Conductor:

Stranded bare copper (class 2)

Insulation:

Cross-linked halogen free (SH)

Assembling tape (optional):

Overall screen:

Copper wire braid (CWB)

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: white

Core identification

Black cores printed with white numbers

Marking

LYNXEO 279 Nber of pairs, triads or quads & cross-section Cu EG CST 74 C 068 00 K3 SH 0.15/0.25 (0.3) kV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754-1



Rated Voltage Uo/U
(Um)
150 / 250 (300) V



Standard
IEC 60332-3-23 (B)
NF C 32070 C1; IEC
60332-3-24 (cat.B)
Quality insurance according of RCC-E



Smoke density
EN/IEC 61034-2



Electro magnetic
interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	Halogen free
Halogen free	IEC 60754-1

Dimensional characteristics

Conductor cross-section	0.5 mm ²
-------------------------	---------------------

Electrical characteristics

Rated Voltage U _o /U (Um)	150 / 250 (300) V
--------------------------------------	-------------------

Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SECTION DE 0.5 MM²

Reference	Name	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over screen [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10216802	74C068 SH M 1P0.5 Cu2 K3 150/250V EG NA	0.9	1.9	4.8	6.7	7.9	82
	74C068 SH M 1T0,5 Cu2 K3 150/250V EG NA	0.9	1.9	4.9	7.2	8.5	99
	74C068 SH M 2P0,5 (QE) Cu2 K3 150/250V EG NA	0.9	1.9	5.0	7.4	9.2	114
	74C068 SH M 1Q0,5 Cu2 K3 150/250V EG NA	0.9	1.9	5.3	7.4	9.2	114
	74C068 SH M 2T0,5 Cu2 K3 150/250V EG NA	0.9	1.9	7.5	10.1	11.2	172
10216803	74C068 SH M 2P0,5 Cu2 K3 150/250V EG NA	0.9	1.9	8.0	10.4	12.0	153
	74C068 SH M 3T0,5 Cu2 K3 150/250V EG NA	0.9	1.9	9.5	12.3	13.8	236



Halogen free
IEC 60754-1



Rated Voltage U_o/U (Um)
150 / 250 (300) V



Fire retardant
NF C 32070 C1; IEC 60332-3-24 (cat.B)



Smoke density
EN/IEC 61034-2



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in service
90 °C

Reference Name	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over screen [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
74C068 SH M 6P0,5 Cu2 K3 150/250V EG NA	0.9	1.9	11.3	14.0	15.5	310
74C068 SH M 6T0,5 Cu2 K3 150/250V EG NA	0.9	1.9	12.5	16.2	18.3	435
74C068 SH M 12P0,5 Cu2 K3 150/250V EG NA	0.9	1.9	14.9	18.1	20.0	525

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

2 pair cables (QE) assembled as a quad (1, 3, 2, 4)

Marking

LYNXEO 279 Nber of pairs, triads or quads & cross-section Cu EG CST 74 C 068 00 K3 SH 0.15/0.25 (0.3)
KV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754-1



Rated Voltage U_o/U_m
(Um)
150 / 250 (300) V



Fire retardant
NF C 32070 C1; IEC
60332-3-24 (cat.B)



Smoke density
EN/IEC 61034-2



Electro magnetic
interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C