

CHARACTERISTICS**Elektrische Eigenschaften**

Maximale Betriebsfrequenz	- MHz
Betriebsspannung Vo DC	28 V
Max. DC resistance of the conductor at 20°C (Ohm/km)	-
Operating voltage between phase and neutral	115 V
Operating voltage between phases	200 V

Anwendungsmerkmale

Betriebstemperatur	-55 ... 260 °C
Ölbeständig	Very good resistance to aircraft fluids
Arc tracking resistant	Ja



Betriebstemp.
-55 ... 260 °C



Ölbeständig
Very good resistance to aircraft fluids

IDENTIFICATIONCores

One core (MLA)	: White except code 001 : Light Yellow code 004 : Light Green
Two cores (MLB)	: Red - Blue
Three cores (MLC)	: Red - Blue - Yellow
Four cores (MLD)	: Red - Blue - Yellow - green
Marking	: EN DRA ++ FRF **
Colour of marking	: White for red and green core, Green for blue and yellow core

Jacket

Colour	: White except code 002, 006, 012 : Light Blue
Marking	: EN xxx ++ FRF **
Colour of marking	: Green

xxx : Short designation (MLA, MLB, MLC, MLD)
++ : AWG
FR : Country of Origin (FR = France)
F : Manufacturer (F = Nexans)
** : Year of manufacturing (ie 14 = 2014)