

CHARACTERISTICS

Características eléctricas

Maximal operating frequency	- MHz
Max. DC resistance of the conductor at 20°C (Ohm/km)	-
Operating Voltage Vo DC	28 V
Operating voltage between phase and neutral	115 V
Operating voltage between phases	200 V

Características de uso

Temperatura ambiente de utilización (rango)	-55 ... 260 °C
Resistencia a aceites	Very good resistance to aircraft fluids
Arc tracking resistant	Yes



Temp. ambiente de utilización
-55 ... 260 °C



Resistencia a aceites
Very good resistance to aircraft fluids

IDENTIFICATIONCores

One core (MLA)	: White except code 001 : Light Yellow code 004 : Light Green
Two cores (MLB)	: Red - Blue
Three cores (MLC)	: Red - Blue - Yellow
Four cores (MLD)	: Red - Blue - Yellow - green
Marking	: EN DRA ++ FRF **
Colour of marking	: White for red and green core, Green for blue and yellow core

Jacket

Colour	: White except code 002, 006, 012 : Light Blue
Marking	: EN xxx ++ FRF **
Colour of marking	: Green
	xxx : Short designation (MLA, MLB, MLC, MLD)
	++ : AWG
	FR : Country of Origin (FR = France)
	F : Manufacturer (F = Nexans)
	** : Year of manufacturing (ie 14 = 2014)