



### CONTACT

Market information  
[industryprojects.business@lynxeogroup.com](mailto:industryprojects.business@lynxeogroup.com)

180 ° C Operating Temperature  
 Nickel Plated Aluminium  
 Power Feeder Cables

Aero engine services.

### STANDARDS

National ESW 1000 - 010

Cable Design

CONDUCTOR  
 A Stranded Conductor  
 Made of Nickel Plated Aluminium

INSULATION  
 Polyimide Tape  
 PTFE Tapes  
 PTFE Coated Fiberglass Tape  
 PTFE Tapes

IDENTIFICATION  
 Colour of cable : white  
 colour of marking : Green

Marking text : " ET xxxxxx FRF++ "  
 xxxxxx=Study number  
 ++ = Year of manufacturing

## CHARACTERISTICS

Maximum cable diameter	- mm
Operating voltage	600 V
操作度范	- 65 ... 180 ° C
Oil resistance	Very good resistance to aircraft fluids



Operating temp.  
 -65 ... 180 ° C



Oil resistance  
 Very good resistance to aircraft fluids

### SELLING AND DELIVERY INFORMATION

Colour of cable : white  
colour of marking : Green

Marking text : " ET xxxxxx FRF++ "

(xxxxxx)= Study number  
++ = Year of manufacturing



Operating temp.  
-65 ... 180 °C



Oil resistance  
Very good resistance to aircraft fluids