



### CONTACT

Market information  
 industryprojects.business@lynx  
 ogroup.com

Fireproof Cable, Single and Multi-cores Screened and Jacketed

**Use in essential services**

### STANDARDS

**National** ESW 1253; ESW 1252

#### CORE

Stranded conductor  
 Nickel clad copper alloy (ESW1252)  
 Nickel clad copper (ESW1253)  
 004: 19x0.15 mm  
 006: 19x0.20 mm  
 010: 19x0.25 mm  
 012: 19x0.30 mm

#### INSULATION

Fireproof insulation  
 Polyimide Tape  
 PTFE Tape

#### SCREEN

Nickel plated copper braid

#### JACKET

PTFE tape(s)

## CHARACTERISTICS

### Electrical characteristics

Operating voltage 600 V

### Usage characteristics

Operating temperature, range -65 ... 260 °C

Fire resistant -

Oil resistance Very good resistance to aircraft fluids

## SELLING AND DELIVERY INFORMATION

### CORE IDENTIFICATION :

Single core : White  
 Two cores : Red - Blue  
 Three cores : Red - Blue - Yellow



Operating temp.  
 -65 ... 260 °C



Fire resistant  
 -



Oil resistance  
 Very good resistance to aircraft fluids

Four cores : Red - Blue - Yellow - Green

**JACKET IDENTIFICATION :**  
White with narrow red stripe

Marking text :  
ESW1252-+++ -xxx-FX-FF-\*\*  
ESW1253-+++ -xxx-FX-FF-\*\*

+++ = Form code  
xxx = Size code  
\*\* = Year of production (ie. 14 = 2014)



Operating temp.  
-65 ... 260 °C



Fire resistant  
-



Oil resistance  
**Very good resistance to aircraft fluids**