



### CONTACT

Market information  
[industryprojects.business@lynxogroup.com](mailto:industryprojects.business@lynxogroup.com)

### General Electronic Wiring

75 Ohms, AWG 26 - Twinaxial cable high immunity

### STANDARDS

Produit ASNE 0849 HJ

#### CORE

AWG 26, 19 x 0.10 mm  
 Stranded conductors  
 Nickel plated high strength copper alloy  
 Insulation :  
 Polyimide tape(s)  
 PTFE Topcoat

#### ASSEMBLY

2 cores twisted

#### SHIELD

0.08 mm Nickel plated copper braid

High immunity tapes

0.10 mm Nickel Plated Copper Braid

#### JACKET

FEP

## CHARACTERISTICS

### Caractéristiques d'utilisation

Température ambiante d'utilisation, plage	-65 ... 200 °C
Rayon de courbure minimum - installé	30 mm
Non propagateur de la flamme	FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)
Résistance aux huiles	Bonne



Temp. d'utilisation  
 -65 ... 200 °C



Non propagateur de la flamme  
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Résistance aux huiles  
 Bonne

## ELECTRICAL AND HIGH FREQUENCY PERFORMANCES

Voltage rating	: 600V rms
Max impedance	: 75 Ohms
Transfer impedance	: 28 mOhms/m DC current
	: 8.70 mOhms/m at 10 kHz
	: 0.85 mOhms/m at 100 kHz
	: 0.008 mOhms/m at 2 MHz

## IDENTIFICATION

Color of cores	: Light Blue, Red
Color of jacket	: White
Black marking of the external sheath	: "HJ 26 FR F ***"
With	(FR) = Country of Origin (FR = France)
	(F) = Manufacturer (F = Filotex)
	(**) = Year of Manufacturing (ie.14 = 2014)



Temp. d'utilisation  
-65 ... 200 °C



Non propagateur de la flamme  
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Résistance aux huiles  
Bonne