



CONTACT

Market information
industryprojects.business@lynxgroup.com

Designed for general purpose aircraft wiring applications.

Nickel Platted Aluminium Alloy Conductors
 UV laser printable.

STANDARDS

Product ABS 0958; ABS 0949 AD

Test prEN 3475

DESIGN CONSTRUCTION

CONDUCTOR
 Nickel plated aluminium rope - lay conductor

INSULATION
 High performance polyimide tape
 Special UV PTFE tape

IDENTIFICATION

Standard color: Grey

Color of marking : Blue

Marking text: AD ** FR F++

** = AWG

FR = Country of origin (FR = France) F = Manufacturer (F = Lynx^{eo}) ++ = Year of production (i.e. 14 = 2014)

CHARACTERISTICS

Conductor stranding	-
Operating voltage	600 V
Maximal operating frequency	- MHz
操作度范	- 60 ... 180 °C
Oil resistance	Very good resistance to aircraft fluids



Operating temp.
 -60 ... 180 °C



Oil resistance
 Very good resistance to aircraft fluids



RoHS compliant
 Yes

Arc tracking resistant

Yes

RoHS compliant

Yes



Operating temp.
-60 ... 180 °C



Oil resistance
Very good resistance to aircraft fluids



RoHS compliant
Yes