



CONTACT

Market information
industryprojects.business@lynxgroup.com

Designed for general Purpose Aircraft Wiring Applications.

260°C, Screened and Jacketed,
 Light Weight,
 UV cable,
 Arc Tracking Resistant

STANDARDS

Product EN 2267-009; EN 2714-014

DESIGN CONSTRUCTION

CORES

EN 2267-009A
 Polyimide tape

SCREEN

Nickel plated copper braid

JACKET

Polyimide tape
 UV PTFE tape

CHARACTERISTICS

Electrical characteristics

| | |
|-----------------------------|-----------|
| Maximal operating frequency | 0.002 MHz |
| Operating voltage | 600 V |

Usage characteristics

| | |
|------------------------------|---|
| Operating temperature, range | -55 ... 260 °C |
| Flame retardant | FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3) |
| Oil resistance | Very good resistance to aircraft fluids |
| Arc tracking resistant | Yes |



Operating temp.
 -55 ... 260 °C



Flame retardant
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
 Very good resistance to aircraft fluids

IDENTIFICATION

Short Designation

| | |
|----------|-------|
| 4 cores | : MMD |
| 5 cores | : MME |
| 6 cores | : MMF |
| 7 cores | : MMG |
| 8 cores | : MMH |
| 9 cores | : MMJ |
| 10 cores | : MMK |
| 11 cores | : MML |

Cores

| | |
|-------------------|---|
| Colours | : See table on this datasheet |
| Marking | : EN DR A ++ FRF** |
| Colour of marking | : White for Black / Red / Brown / Green and Violet core Green for Blue / Yellow / White / Orange / Grey and Light green core |

Jacket

| | |
|-------------------|-------------------------------|
| Colours | : See table on this datasheet |
| Marking | : EN xxx ++ FRF** |
| Colour of marking | : Green |

xxx = Short designation (MMD, MME, ...)
++ = AWG
FR = Country Origin (FR = France)
F = Manufacturer (F = NEXANS)
** = Year of manufacturing (ie. 19 = 2019)