



CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

50 Ohms, Coaxial Cable

Designed for high frequency radio communications applications in aeronautic environment.

STANDARDS

Test prEN 3475

International prEN 4604-001, -002 and -008

DESIGN CONSTRUCTION

Product designed according to : prEN 4604-001, -002 and -008
Tested according to prEN 3475

CORE

37 x 0.34 mm Strand
Silver plated copper
Diameter = 2.33 ± 0.05 mm

INSULATION

Fluorocarbon
Diameter = 6.0 ± 0.10 mm

SHIELD

Two braids
Silver plated copper 0.13 mm
Diameter = 7.10 ± 0.10 mm

JACKET

Fluoropolymer

Diameter = 7.70 ± 0.20 mm
Nom. weight = 130 g/m
Max. weight = 137 g/m

IDENTIFICATION

Jacket Color : White
Color of the marking : Black

Marking text : " EN WD FRF ** "

FR = Country of Origin (FR = France)
F = Manufacturer (F = Lynxéo)
(**) = Year of manufacturing (i.e. 14 = 2014)



操作温度
-55 ... 200 ° C



Static bending rad.
40 mm



Min. dynamic operating
bending rad.
80.0 mm



阻燃 - 火焰
FAR/JAR part 25 sec 25.869
(a) (4) Appendix F part 1
(3)



耐油
Very good resistance to
aircraft fluids



符合RoHS
是

CHARACTERISTICS

使用特性

操作温度范围	-55 ... 200 ° C
最小弯曲半径 - 静态	40 mm
最小弯曲半径 - 动态	80.0 mm
阻燃 - 火焰	FAR/JAR part 25 sec 25.869 (a) (4) Appendix F part 1 (3)
耐油	Very good resistance to aircraft fluids
符合RoHS	是

ELECTRICAL PERFORMANCES

Operating frequency	: up to 8 GHz
Dielectric strength	: 2500Vac
Corona extinction voltage	: 1500Vac
Insulation resistance	: $\geq 5000 \text{ M}\Omega \cdot \text{km}$
Characteristic impedance at 200 MHz	: $50 \pm 2 \Omega$
Maximum linear capacitance	: 85 pF/m
Nominal velocity of propagation	: 240 000 km/s

HIGH FREQUENCY PERFORMANCES

Frequency (MHz)	Nom. Rated Power (W)	Max. Attenuation at 20° C (dB/100m)	Max. Return Loss
50	5700	5.0	1.1
100	4000	7.2	1.1
150	3100	9.1	1.1
200	2700	10.7	1.15
400	1800	16.1	1.15
1000	1000	28.6	1.15
1600	730	39.6	1.2
2500	530	55.0	1.2
3000	480	61.0	1.2
8000	250	110.0	1.35

TRANSFERT IMPEDANCE

Maximum Values ($m\Omega/m$)	: 4.2 from 0 to 0.01 MHz
	: 4.0 at 0.1 MHz
	: 1.3 at 1 MHz
	: 0.6 at 5 MHz
	: 1.0 at 10 MHz
	: 2.3 at 30 MHz
	: 5.5 at 100 MHz