



### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.com  
ogroup.com

CAN-BUS cables with PVC jacket for fixed installation, shielded, flame retardant

### STANDARDS

**Product** UL and CSA approval

### APPLICATIONS

Interconnecting fieldbus cable for static application  
BUS cables to connect Controller Area Network components

### Normative references

**CAN standard and customers requirements**  
**UL recognized / CSA approval**



Operating temp.  
-20 ... 80 °C



Storage temperature, range  
-30 ... 80 °C



Flame retardant  
IEC/EN 60332-1-2; FT1; UL 1581 FT1

## CHARACTERISTICS

### Construction characteristics

Conductor material	Bare copper
Insulation	Foam-skin
Insulation colour	DIN 47100
Taping	Soft tape
Shielding	≥85% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Violet RAL 4001

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U	300 V
Characteristic impedance	120 Ohm
Test voltage	1500 V

### Transmission characteristics

Attenuation at 1 MHz	1.3 dB/100m
Attenuation at 5 MHz	3.1 dB/100m
Attenuation at 10 MHz	4.3 dB/100m
Attenuation at 20 MHz	6.4 dB/100m

### Usage characteristics

Field of application	Static
Operating temperature, range	-20 ... 80 °C
Storage temperature, range	-30 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1

## PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Nominal outer diameter [mm]	Copper content [kg/km]
☎ 13-DRX24P01R	13-DRX24P01R	CAN BUS PVC (1x2x0.22)C	(1x2x0.22)C	5.7	17
☎ 13-DRX24P02R	13-DRX24P02R	CAN BUS PVC (2x2x0.22)C	(2x2x0.22)C	7.6	35

☎ = Make to order, 🏠 = In stock,