



Servo cables with control pair for dynamic applications, PVC jacket, shielded, resistant to oils, flame retardant

STANDARDS

Product UL and CSA approval

Normative references:

UL recognised / CSA
 AWM 80°C - 600V/1000V
 AWM 80°C - 600V/1000V FT1

Oil resistance

IEC 50363-4-1

Flame retardant

IEC 60331-1-2; FT1; UL 1581; EN 50265-2-1

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

CHARACTERISTICS

Construction characteristics

Conductor material	Stranded bare copper
Insulation	Polyolefin
Insulation colour	Power: U/L1/C/L+ V/L2 W/L3/D/L- Ye/GN; Signal: Black - White
Lay Up	power cores and control pairs stranded with filler
Taping	Non woven tape
Shielding	80% tinned copper braid coverage
Outer sheath	PVC
Sheath colour	Orange RAL 2003

Electrical characteristics

Rated Voltage Uo/U	0.6/1 kV
Test voltage	4000 V

Mechanical characteristics

Maximum acceleration	15 m/s ²
Bending cycles	5 Mio.
Speed	180 m/min



Operating temp.
 -15 ... 80 °C



Storage temperature, range
 -20 ... 80 °C



Oil resistance
 EN 50363-4-1



Flame retardant
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-20 ... 80 °C
Oil resistance	EN 50363-4-1
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Nominal outer diameter [mm]	Copper content [kg/km]
☎ 13-EYS02Z06R-A5	13-EYS02Z06R-A5	13-EYS (4G35 + (2x1,5)C)C	(4G35 + (2x1.5)C)C	30.9	1570
☎ 10553259	13-EYS03Z06R-A5	13-EYS (4G25 + (2x1,5)C)C	(4G2.5 + (2x1.5)C)C	26.6	1166
📦 10553265	13-EYS05Z06R-A5	13-EYS (4G16 + (2x1,5)C)C	(4G16 + (2x1.5)C)C	23.1	803
📦 10553272	13-EYS07Z06R-A5	13-EYS (4G10 + (2x1,5)C)C	(4G10 + (2x1.5)C)C	19.4	560
📦 10553274	13-EYS09Z06R-A5	13-EYS (4G6 + (2x1,5)C)C	(4G6 + (2x1.5)C)C	16.8	364
📦 10553277	13-EYS11Z06R-A5	13-EYS (4G4 + (2x1,5)C)C	(4G4 + (2x1.5)C)C	14.8	272
📦 10553281	13-EYS13Z06R-A5	13-EYS (4G2,50 + (2x1,5)C)C	(4G2.5 + (2x1.5)C)C	13.4	204
📦 10553284	13-EYS15Z06R-A5	13-EYS (4G1,50 + (2x1,5)C)C	(4G1.5 + (2x1.5)C)C	11.6	155
☎ 13-EYS01Z06R-A5	13-EYS01Z06R-A5	13-EYS (4G50 + (2x1,5)C)C	(4G50 + (2x1.5)C)C	34.0	2299

☎ = Make to order, 📦 = In stock,



Operating temp.
-15 ... 80 °C



Storage temperature, range
-20 ... 80 °C



Oil resistance
EN 50363-4-1



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1