



CONTACT

Market information
industryprojects.business@lynxeogroup.com

Digital feedback cables according to SIEMENS DRIVE CLiQ standard

STANDARDS

Product UL and CSA approval

DESIGN

Element 2x2x0.22 mm²

Conductor

Bare copper stranded

Insulation

Foam-skin PE

Colour code

(Blu + Pink)+(Yellow + Green)

Element 2x2x0.15 mm²

Conductor

Bare stranded copper

Insulation

Foam-skin PE

Colour code

(Blu + Pink)+(Yellow + Green)

Element 1x2x0.38 mm²

Conductor

Tinned stranded copper

Insulation

Polyolefin

Colour code

(Red + Black)

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Shielding	≥85% tinned copper braid coverage



Operating temp.
-20 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1

Construction characteristics

Taping	Non woven tape
Sheath colour	Green RAL 6018

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	500 V

Usage characteristics

Operating temperature, range	-20 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Nominal outer diameter [mm]	Copper content [kg/km]
10554179	13-MYS22X06R-V2	DRIVE CLIQ (2x2x0.22+1x2x0.38)C PVC	(2x2x0.22+1x2x0.38)C	7.2	37
10554365	13-MYS22X06P-V1	DRIVE CLIQ (2x2x0.15+1x2x0.38)C PUR	(2x2x0.15+2x0.38)C	7.0	37
10554181	13-MYS24P02R-V1	DRIVE CLIQ (2x2x0,22)C PVC	(2x2x0.22)C	6.85	25

= Make to order, = In stock,



Operating temp.
-20 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1