



CONTACT

Market information
 industryprojects.business@lynxéo
 ogroup.com

Digital feedback cables according to SIEMENS DRIVE CLiQ standard

STANDARDS

Product UL and CSA approval

DESIGN

Double Pair element: 2x2x...mm²

Conductor
 Bare copper stranded

Insulation
 Polyolefin compound

Colour code
 (Blu + Pink)+(Yellow + Green)

Single pair element: 1x2x0.38 mm²

Conductor
 Tinned stranded copper

Insulation
 Polyolefin

Colour code
 (Red + Black)

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Insulation	Polyolefin
Insulation colour	See Tab
Lay Up	Please request detailed data sheet
Shielding	≥85% tinned copper braid coverage
Taping	Non woven tape
Sheath colour	Green RAL 6018

Electrical characteristics

Rated Voltage Uo/U	30 V
Test voltage	500 V



Operating temp.
 -20 ... 80 °C



Oil resistance
 EN 50363-10-2



Flame retardant
 IEC/EN 60332-1-2; FT1; UL 1581 FT1

Usage characteristics

Operating temperature, range	-20 ... 80 °C
Oil resistance	EN 50363-10-2
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Nominal outer diameter [mm]	Copper content [kg/km]
10563699	-	DRIVE CLIQ (2x2x0,20 +1x2x0,38) PUR	(2x(2x0,22)C+(2x0,38)C)C	7.0	37
10554179	13-MYS22X06R-V2	DRIVE CLIQ (2x2x0.22 +1x2x0.38)C PVC	(2x2x0.22+1x2x0.38)C	7.2	37
10554365	13-MYS22X06P-V1	DRIVE CLIQ (2x2x0.15 +1x2x0.38)C PUR	(2x2x0.15+2x0.38)C	7.0	37
10554181	13-MYS24P02R-V1	DRIVE CLIQ (2x2x0,22)C PVC	(2x2x0.22)C	6.85	25

= Make to order, = In stock,



Operating temp.
-20 ... 80 °C



Oil resistance
EN 50363-10-2



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1