



Servo cables for extremely dynamic applications. MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

Servo cables for extremely dynamic applications; PUR jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
 industryprojects.business@lyn
 xeogroup.com



无卤
是



操作温度
-30 ... 80 ° C



存储温度范围
-50 ... 80 ° C



阻燃 - 火焰
IEC 60332-1-2; UL 1581 FT1



耐油
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

结构特性

导体材料	Bending-resistant conductor with bare copper wires
绝缘	TPM with very low capacitance
绞合	
绝缘色	Black - white marking U/L1/C/L + V/L2 W/L3/D/L - Yellow/Green
屏蔽	Tinned copper braid, coverage \geq 85%
外护套	PUR
护套颜色	Orange RAL 2003
无卤	是

电气特性

Rated Voltage U ₀ /U	0.6/1 kV
测试电压	4000 V

机械特性

弯曲循环	5 Mio.
速度	300 m/min
Maximum acceleration	50 m/s ²

使用特性

应用类型	动态
最小弯曲半径 - 动态	7.5 (xD)
操作温度范围	-30 ... 80 ° C
存储温度范围	-50 ... 80 ° C
阻燃 - 火焰	IEC 60332-1-2; UL 1581 FT1
耐油	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name	结构类型	外径 [mm]	铜含量 [kg/km]
☎ 49403061	-	SERVO CABLES WITH LOW CAPACITANCE ACC. TO SEW® STANDARD (4G1, 5) C	4G1.5 C	12	95
☎ 49403261	-	SERVO CABLES WITH LOW CAPACITANCE ACC. TO SEW® STANDARD (4G2, 5) C	4G2.5 C	14.1	148

☎ = Make to order, 📦 = In stock,