



Measuring systems cables for extremely dynamic applications. MOTIONLINE® PREMIUM

### STANDARDS

Product UL and CSA approval

For extremely dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

### CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com



无卤  
是



操作温度  
-30 ... 80 ° C



存储温度范围  
-40 ... 80 ° C



阻燃 - 火焰  
IEC 60332-1-2; UL 1581 FT1



耐油  
DIN EN 50363-10-2 & DIN EN 60811-404

### CHARACTERISTICS

#### 结构特性

导体材料	Bending-resistant conductor with tinned copper wires
绝缘	TPM with very low capacitance
绝缘色	See Tab
屏蔽	Tinned copper braid, coverage $\geq$ 85%
外护套	PUR
护套颜色	Green RAL 6018
无卤	是

#### 电气特性

Rated Voltage U <sub>0</sub> /U	30 V
测试电压	300 V

#### 机械特性

弯曲循环	5 Mio.
速度	300 m/min
Maximum acceleration	50 m/s <sup>2</sup>

#### 使用特性

应用类型	动态
最小弯曲半径 - 动态	7.5 (xD)
操作温度范围	-30 ... 80 ° C
存储温度范围	-40 ... 80 ° C
阻燃 - 火焰	IEC 60332-1-2; UL 1581 FT1
耐油	DIN EN 50363-10-2 & DIN EN 60811-404

### PRODUCT LIST

Reference	Country Ref.	Name	结构类型	外径 [mm]	铜含量 [kg/km]
☎ 49492971	6FX8008-1BD41	MEASURING SYSTEMS SIEMENS® STANDARD 6FX8008+ (3x (2x0, 14) C+2x0, 5+4x0, 14) C	(3x (2x0, 14) C+2x0, 5+4x0, 14) C	9.5	67
☎ 49492871	6FX8008-1BD51	MEASURING SYSTEMS SIEMENS® STANDARD 6FX8008+ (3x (2x0, 14) C+2x0, 5+4x0, 14+4x0, 22) C	(3x (2x0, 14) C+2x0, 5+4x0, 14+4x0, 22) C	10	78

☎ = Make to order, 📦 = In stock,