



Measuring systems cables for extremely dynamic applications. MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

For extremely dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
industryprojects.business@lynxeogroup.com



Halogen free
Yes



Operating temp.
-30 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	300 V

Mechanical characteristics

Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Outer Diameter [mm]	Copper content [kg/km]
☎ 49492971	6FX8008-1BD41	MEASURING SYSTEMS SIEMENS® STANDARD 6FX8008+ (3x(2x0,14)C +2x0,5+4x0,14)C	(3x(2x0,14)C+2x0,5+4x0,14)C	9.5	67
☎ 49492871	6FX8008-1BD51	MEASURING SYSTEMS SIEMENS® STANDARD 6FX8008+ (3x(2x0,14)C +2x0,5+4x0,14+4x0,22)C	(3x(2x0,14)C+2x0,5+4x0,14+4x0,22)C	10	78

☎ = Make to order, 📦 = In stock,