



Measuring system cables for extremely dynamic applications. MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

For extremely dynamic applications; PUR Jacket, screened, inner jacket, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
industryprojects.business@lynxgroup.com



Halogen free
Yes



Operating temp.
 -30 ... 80 °C



Storage temperature, range
 -40 ... 80 °C



Flame retardant
 IEC 60332-1-2; UL 1581 FT1



Oil resistance
 DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	See Tab
Inner sheath	TPE compound, optimized for drag chain use
Screen	Tinned copper braid, coverage ≥ 80%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	300 V

Mechanical characteristics

Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Copper content [kg/km]	Approximate weight [kg/km]
☎ 49329071	-	MEASURING SYSTEM CABLES SEW® STANDARD (6x2x0,25)C inner jacket	(6x2x0,25)C	60	124
☎ 49326671	-	MEASURING SYSTEM CABLES SEW® STANDARD (5x2x0,25)C inner jacket	(5x2x0,25)C	53	114
☎ 49329073	-	MEASURING SYSTEM CABLES SEW® STANDARD (6x2x0,25)C	(6x2x0,25)C	59	101
☎ 49326673	-	MEASURING SYSTEM CABLES SEW® STANDARD (5x2x0,25)C	(5x2x0,25)C	52	90

☎ = Make to order, 📦 = In stock,