

Home run cables for extremely dynamic applications MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

Home run cables for extremely dynamic applications; PUR Jacket; resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC - and halogen - free.



CONTACT

Market information
industryprojects.business@lynxeogroup.com



Halogen free



Operating temp.
 -30 ... 80 °C



Storage temperature, range
 -50 ... 80 °C



Oil resistance
 IEC 60332 - 1 - 2; UL 1581 FT1
 DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404



CHARACTERISTICS

	Bending - resistant conductor with bare copper wires
	TPM with very low capacitance
Lay Up	cores stranded with filler
Insulation colour	See Tab
	PUR
Sheath colour	Black - RAL 9005
Halogen free	
Rated Voltage U ₀ /U	300 V 2000 V
Bending cycles	5 Mio.
Speed	300 m/min
Maximum acceleration	50 m/s ²
Field of application	Dynamic
Minimum dynamic operating bending radius	7.5 (xD)
操作度范	- 30 ... 80 ° C
Storage temperature, range	- 50 ... 80 ° C
	IEC 60332 - 1 - 2; UL 1581 FT1
Oil resistance	DIN EN 50363 - 10 - 2 & DIN EN 60811 - 404

PRODUCT LIST

Reference	Country Ref.	Name		Copper content [kg/km]	() [kg/km]
☎ 44401310	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION 8x0,34+3x1,0	8x0,34+3x1,0	60	110
☎ 44401410	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION 12x0,34+3x1,0	12x0,34+3x1,0	72	120
☎ 44401510	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION 16x0,34+3x1,0	16x0,34+3x1,0	88	140
☎ 44401610	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION 16x0,5+3x1,0	16x0,5+3x1,0	107	164

☎ = Make to order, 📦 = In stock,