

Home run cables for very dynamic applications MOTIONLINE® ADVANCED

### STANDARDS

**Product** UL and CSA approval

Home run cables for very dynamic applications; PUR Jacket; resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.



### CONTACT

Market information  
[industryprojects.business@lynxeogroup.com](mailto:industryprojects.business@lynxeogroup.com)



Halogen free  
**Yes**



Operating temp.  
 -15 ... 80 °C



Storage temperature, range  
 -40 ... 80 °C



Flame retardant  
 IEC 60332-1-2; UL 1581 FT1



Oil resistance  
 DIN EN 50363-10-2 & DIN EN 60811-404

## CHARACTERISTICS

### Construction characteristics

Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Lay Up	cores stranded with filler
Insulation colour	See Tab
Outer sheath	PUR
Sheath colour	Black - RAL 9005
Halogen free	Yes

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U	300 V
Test voltage	2000 V

### Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s <sup>2</sup>

### Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404

## PRODUCT LIST

Reference	Country Ref.	Name
☎	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED 8x0,34+3x1,0
☎ 44487611	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED 12x0,34+3x1,0
☎	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED 8x0,34+3x1,0
☎ 44487211	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED 16x0,34+3x1,0
☎ 44494811	-	HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED 16x0,5+3x1,0

☎ = Make to order, 📦 = In stock,