



Cavi Ethernet industriali per applicazioni in torsione estrema MOTIONLINE® PREMIUM

STANDARDS

Product UL and CSA approval

Industrial Ethernet cables for extrem torsion applications; PUR jacket, TPM insulation, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
industryprojects.business@lynxe
ogroup.com



Senza alogeno
Y



Temperatura Operativa
-30 ... 80 °C



Temperatura di stoccaggio, intervallo
-40 ... 80 °C



Ritardante la fiamma
IEC 60332-1-2; UL 1581 FT1



Resistenza all'olio
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Caratteristiche costruttive

Materiale del conduttore	Conduttore resistente alla flessione con fili di rame nudo
Isolamento	TPM con capacità molto bassa
Formazione	Nuclei intrecciati a coppie con filler, Coppie intrecciate con filler
Colore dell'isolamento	Si prega di richiedere la scheda tecnica dettagliata
Schermo	Foglio schermato e spirale di rame stagnato, copertura \geq 90%
Guaina esterna	PUR
Colore della guaina esterna	Verde RAL 6018
Senza alogeno	Y

Caratteristiche elettriche

Tensione nominale U _o /U	30 V
Tensione di prova	500 V

Caratteristiche meccaniche

Torsion test max. +/- 4 turns for 10 meters	180°/m
Cicli di curvatura	5 Mio.
Velocità di traslazione	180° / s

Caratteristiche d'utilizzo

Campo d'applicazione	Dinamica
Temperatura Operativa	-30 ... 80 °C
Temperatura di stoccaggio, intervallo	-40 ... 80 °C
Ritardante la fiamma	IEC 60332-1-2; UL 1581 FT1
Resistenza all'olio	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name	Costruzione	Diametro esterno [mm]	Quantitativo rame [kg/km]
☎ 44467479	-	INDUSTRIAL ETHERNET CABLES FOR ROBOT APPLICATION (2x2x0,18)StD - Ethernet CAT5e	(2x2x0,18)StD - Ethernet CAT5e	7	21
☎ 44484670	-	INDUSTRIAL ETHERNET CABLES FOR ROBOT APPLICATION (4x2x0,18)StD - Ethernet CAT5e	(4x2x0,18)StD - Ethernet CAT5e	7,6	30

☎ = Make to order, 📦 = In stock,