



For advanced dynamic applications MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

For advanced dynamic applications; screened cables; PUR sheath, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC and halogen free, Industry 4.0 ready.

CONTACT

Market information
industryprojects.business@lynxeogroup.com



Operating temp.
-15 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC/EN 60332-1-2; FT1; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Conductor material	Bending-resistant conductor with bare copper wires
Insulation	Polyolefin
Lay Up	Star Quad and power cores stranded with fillers
Insulation colour	White, Orange, Blue, Yellow
Inner sheath	Halogen free polymer compound
Taping	Plastic aluminium tape
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018

Electrical characteristics

Rated Voltage U _o /U	30 V
Test voltage	500 V
Characteristic impedance	100 Ohm

Mechanical characteristics

Bending cycles	5 Mio.
Speed	180 m/min
Maximum acceleration	20 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC/EN 60332-1-2; FT1; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Outer Diameter [mm]	Copper content [kg/km]
☎ 44491770	-	PROFINET TYPE C CABLES (1x4xAWG22/7)C	(1x4xAWG22/7)C	6.9	34
☎ 44499079	-	PROFINET TYPE C CABLES (1x4xAWG22/7)C+4x1,5	(1x4xAWG22/7)C+4x1,5	10.6	76

☎ = Make to order, 📦 = In stock,