



For dynamic applications MOTIONLINE® STANDARD

STANDARDS

Product UL and CSA approval

For standard dynamic applications; screened cables; PUR sheath, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC and halogen free, Industry 4.0 ready.

CONTACT

Market information
industryprojects.business@lynxeogroup.com



Halogen free
Yes



Operating temp.
 -30 ... 80 °C



Storage temperature, range
 -40 ... 80 °C



Flame retardant
 IEC 60332-1-2; UL 1581 FT1



Oil resistance
 DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Construction type	(4x2xAWG26/19)C
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	Polyolefin
Lay Up	Pairs stranded with fillers
Insulation colour	White/Orange, White/Green, White/Blue, White/Brown
Taping	Plastic aluminium tape
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Green RAL 6018
Halogen free	Yes

Dimensional characteristics

Outer Diameter	6.8 mm
Copper content	27 kg/km
Approximate weight	54 kg/km

Electrical characteristics

Rated Voltage U _o /U	30 V
Test voltage	500 V
Characteristic impedance	100 Ohm

Mechanical characteristics



Bending cycles	1 Mio.
Speed	120 m/min
Maximum acceleration	2 m/s ²

Usage characteristics

Field of application	Dynamic
Minimum dynamic operating bending radius	15 (xD)
Operating temperature, range	-30 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name
 44495170	-	INDUSTRIAL ETHERNET CAT5e STANDARD (4x2xAWG26/19)C

 = Make to order,  = In stock,