



For fixed installations MOTIONLINE® STANDARD

Rubber Jacket; flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free

CONTACT

Market information
industryprojects.business@lynx
ogroup.com



Storage temperature, range
-40 ... 80 °C



Operating temp.
-40 ... 85 °C



Oil resistance
EN 50363-4-1

CHARACTERISTICS

Construction characteristics

Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	Rubber
Insulation colour	Brown-Blue
Outer sheath	Rubber

Electrical characteristics

Test voltage	300 V
--------------	-------

Usage characteristics

Field of application	Fixed installations
Minimum Bending Radius during installation	9 (xD)
Storage temperature, range	-40 ... 80 °C
Operating temperature, range	-40 ... 85 °C
Oil resistance	EN 50363-4-1

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Copper content [kg/km]	Approximate weight [kg/km]
☎ 48210165	-	AS-INTERFACE RUBBER FLAT CABLE 2x1,5 Yellow	2 x 1.50	29	70
☎ 48210116	-	AS-INTERFACE RUBBER FLAT CABLE 2x1,5 Black	2 x 1.50	29	70
☎ 48213165	-	AS-INTERFACE RUBBER FLAT CABLE 2x2,5 Yellow	2 x 2.50	48	84
☎ 48213115	-	AS-INTERFACE RUBBER FLAT CABLE 2x2,5 Black	2 x 2.50	48	84

☎ = Make to order, 📦 = In stock,