



For fixed installations MOTIONLINE® STANDARD

Rubber Jacket; flame retardant, resistant to hydrolysis and microbes, PVC - and halogen - free

### CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com



Storage temperature, range  
-40 ... 80 °C



Operating temp.  
-40 ... 85 °C



Oil resistance  
EN 50363 -4 -1

## CHARACTERISTICS

Bending - resistant conductor with tinned copper wires

Insulation colour

Brown - Blue

300 V

Field of application

Fixed installations

Minimum Bending Radius during installation

9 (xD)

Storage temperature, range

- 40 ... 80 ° C

操作度范

- 40 ... 85 ° C

Oil resistance

EN 50363 - 4 - 1

## PRODUCT LIST

Reference	Country Ref.	Name	Copper content [kg/km]	( ) [kg/km]
☎ 48210165	-	AS - INTERFACE RUBBER FLAT CABLE 2x1,5 Yellow	2 x 1.50 29	70
☎ 48210116	-	AS - INTERFACE RUBBER FLAT CABLE 2x1,5 Black	2 x 1.50 29	70
☎ 48213165	-	AS - INTERFACE RUBBER FLAT CABLE 2x2,5 Yellow	2 x 2.50 48	84
☎ 48213115	-	AS - INTERFACE RUBBER FLAT CABLE 2x2,5 Black	2 x 2.50 48	84

☎ = Make to order, 📦 = In stock,