



For fixed installations MOTIONLINE® STANDARD

Rubber Jacket; flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com



存储温度范围
-40 ... 80 ° C



操作温度
-40 ... 85 ° C



耐油
EN 50363-4-1

CHARACTERISTICS

结构特性	
导体材料	Bending-resistant conductor with tinned copper wires
绝缘	橡胶
绝缘色	Brown-Blue
外护套	橡胶
电气特性	
测试电压	300 V
使用特性	
应用类型	固定安装
最小弯曲半径 - 安装	9 (xD)
存储温度范围	-40 ... 80 ° C
操作温度范围	-40 ... 85 ° C
耐油	EN 50363-4-1

PRODUCT LIST

Reference	Country Ref.	Name	结构类型	铜含量 [kg/km]	近似重量 [kg/km]
☎ 48210165	-	AS-INTERFACE RUBBER FLAT CABLE 2x1,5 Yellow	2 x 1.50	29	70
☎ 48210116	-	AS-INTERFACE RUBBER FLAT CABLE 2x1,5 Black	2 x 1.50	29	70
☎ 48213165	-	AS-INTERFACE RUBBER FLAT CABLE 2x2,5 Yellow	2 x 2.50	48	84
☎ 48213115	-	AS-INTERFACE RUBBER FLAT CABLE 2x2,5 Black	2 x 2.50	48	84

☎ = Make to order, 📦 = In stock,