



For fixed installations MOTIONLINE® STANDARD

Rubber Jacket; flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free

CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com



Température de stockage, plage
-40 ... 80 °C



Temp. d'utilisation
-40 ... 85 °C



Résistance aux huiles
EN 50363-4-1

CHARACTERISTICS

Caractéristiques de construction

Nature de l'âme	Bending-resistant conductor with tinned copper wires
Isolation	caoutchouc
Couleur d'isolation	Brown-Blue
Gaine extérieure	caoutchouc

Caractéristiques électriques

Tension d'essai	300 V
-----------------	-------

Caractéristiques d'utilisation

Application	Installations fixes
Minimum Bending Radius during installation	9 (xD)
Température de stockage, plage	-40 ... 80 °C
Température ambiante d'utilisation, plage	-40 ... 85 °C
Résistance aux huiles	EN 50363-4-1

PRODUCT LIST

Reference	Country Ref.	Name	Structure	Poids en cuivre [kg/km]	Masse approximative [kg/km]
☎ 48210165	-	AS-INTERFACE RUBBER FLAT CABLE 2x1,5 Yellow	2 x 1.50	29	70
☎ 48210116	-	AS-INTERFACE RUBBER FLAT CABLE 2x1,5 Black	2 x 1.50	29	70
☎ 48213165	-	AS-INTERFACE RUBBER FLAT CABLE 2x2,5 Yellow	2 x 2.50	48	84
☎ 48213115	-	AS-INTERFACE RUBBER FLAT CABLE 2x2,5 Black	2 x 2.50	48	84

☎ = Make to order, 📦 = In stock,