



Measuring systems cables for very dynamic application MOTIONLINE®

STANDARDS

Product UL and CSA approval

For very dynamic applications; PUR Jacket, screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
industryprojects.business@lynx^{eo}
ogroup.com



Operating temp.
-15 ... 80 °C



Storage temperature, range
-40 ... 80 °C



Flame retardant
IEC 60332-1-2; UL 1581 FT1



Oil resistance
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Conductor material	Bending-resistant conductor with tinned copper wires
Insulation	TPM with very low capacitance
Insulation colour	1^ Pair: Green+Yellow; 2^ Pair: Pink+Blue
Taping	Copper/Polyester Tape
Screen	Tinned copper braid, coverage ≥ 85%
Outer sheath	PUR
Sheath colour	Grey

Dimensional characteristics

Outer Diameter	7.1 mm
----------------	--------

Electrical characteristics

Rated Voltage U ₀ /U	30 V
Test voltage	300 V

Mechanical characteristics

Maximum acceleration	20 m/s ²
Bending cycles	5 Mio.
Speed	180 m/min

Usage characteristics

Field of application	Fixed installations
Minimum dynamic operating bending radius	10 (xD)
Operating temperature, range	-15 ... 80 °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404

PRODUCT LIST

Reference	Country Ref.	Name	Construction type	Copper content [kg/km]	Approximate weight [kg/km]
☎ 44460479	6FX8008-2DC00	DRIVE CLiQ CABLE ACC. TO SIEMENS® 6FX8008-2DC00 (2x(2x0,22)C+(2x0,38)C)C C+(2x0,38)C)C	(2x(2x0,22)C+(2x0,38)C)C	37	67
☎ 44495079	6FX8008-2DC00	DRIVE CLiQ CABLE ACC. TO SIEMENS® 6FX8008-2DC00 (2x(2x0,15)C+(2x0,38)C)C C+(2x0,38)C)C	(2x(2x0,15)C+(2x0,38)C)C	42	62

☎ = Make to order, 📦 = In stock,