



CONTACT

Market information
 industryprojects.business@lynxéo
 ogroup.com

Designed for general Purpose Aircraft Wiring Applications.

UV Laser printable Wire
 260°C Operating Temperature Light Weight
 Arc Tracking Resistant

STANDARDS

Product EN 2267-010

DESIGN CONSTRUCTION

CORE

Stranded Conductor : Nickel Plated High

Strength Copper Alloy (AWG 26 & 24) or
 Nickel Plated Copper (AWG 22 to 2)

INSULATION

Special Polyimide Tape
 Special UV PTFE Tape(s)

IDENTIFICATION

Standard colour code :

White except AWG 26 which is light yellow and AWG 22 which is light green
 AWG 24 is available in light blue color (EN2267-010A 002B)

Color of marking: green

Marking text: EN DR ** FR F ++

DR = Short designation

*** = AWG Wire Size*

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 13 = 2013)

CHARACTERISTICS

Electrical characteristics

Maximal operating frequency	0.002 MHz
Operating Voltage Vo DC	28 V
Operating voltage between phase and neutral	115 V
Operating voltage between phases	200 V



Operating temp.
 -55 ... 260 °C

















Oil resistance
 Very good resistance to aircraft fluids

Usage characteristics

Operating temperature, range	-55 ... 260 °C
Oil resistance	Very good resistance to aircraft fluids
Arc tracking resistant	Yes

PRODUCT LIST

Reference	Country Ref.	Name	Conductor cross-section (AWG/KCMIL)	Maximum core diameter [mm]	Maximum outer diameter [mm]
	-	EN 2267-010A 001	26	0.49	0.84
	-	EN 2267-010A 002	24	0.58	0.96
	-	EN 2267-010A 004	22	0.73	1.1
	-	EN 2267-010A 006	20	0.97	1.34
	-	EN 2267-010A 010	16	1.22	1.61
	-	EN 2267-010A 012	18	1.45	1.92
	-	EN 2267-010A 020	14	1.73	2.24
	-	EN 2267-010A 030	12	2.18	2.7
	-	EN 2267-010A 051	10	2.77	3.33
	-	EN 2267-010A 090	8	3.85	4.4
	-	EN 2267-010A 140	6	5.2	5.7
	-	EN 2267-010A 220	4	6.8	7.41
	-	EN 2267-010A 340	2	8.6	9.16

☎ = Make to order,  = In stock,Operating temp.
-55 ... 260 °COil resistance
Very good resistance to aircraft fluids