

CONTACT

Market information
industryprojects.business@lynx
ogroup.com

- 12/20(24)kV
- Non-armoured
- Low smoke, zero halogen (LSZH)

STANDARDS

Test IEC 60332-3-24; NF C32-070/C1

DESIGN

- **Conductor:** Stranded plain copper (class 2)
- **Semi conductor**
- **Insulation:** Ethylene propylene rubber (EPR)
- **Insulation screen:** Semi conductor and copper tapes
- **Outer sheath:** Low smoke, zero halogen (LSZH)

Marking

LYNXEO 279 - EPR/LSZH - 12/20 kV - Nb of cores & cross-section - Cu - MM YYYY - Cca-s1b, d1, a1 - Manufacturing N° + metric marking

Core identification

1x: naturel



Halogen free
IEC 60754-1



Operating temp.
-20 ... 60 °C



Gases corrosivity
IEC 60754-2



Smoke density
IEC 61034-2



Max. conductor temp. in
service
90 °C



Fire retardant
NF C 32-070 C1, IEC 60332-3-24
(cat.C)

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	EPR
Outer sheath	LSZH compound
Halogen free	IEC 60754-1

Dimensional characteristics

Number of cores	1
Conductor cross-section	25 mm ²
Approximate weight	1200 kg/km
Maximum outer diameter	33.0 mm
Minimum outer diameter	29.5 mm

Usage characteristics

Operating temperature, range	-20 ... 60 °C
Gases corrosivity	IEC 60754-2
Smoke density	IEC 61034-2
Max. conductor temperature in service	90 °C
Fire retardant	NF C 32-070 C1, IEC 60332-3-24 (cat.C)

PRODUCT LIST

Reference	Country Ref.	Name
☎ 13110148	-	CU/EPR/LSZH 12/20(24)kV 1x25 Cca

☎ = Make to order, 📦 = In stock,