



Reference: 10553674
Country Ref.: C1250056409
EAN 13: 8054803111625

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

UL-listed tray cables (TC-ER) cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, shielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed. suitable for American and Canadian market

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- cable tray in factories in industry
- Industrial sector
- wind turbine application

Approvals:

UL MTW UL1063

UL TC-ER 90° C 600V UL1277

UL WTTC 90° C 1000V UL2277

UL DP-1

UL AWM 600V

C(UL) C1C/TC

CHARACTERISTICS

结构特性

结构类型	(5G2, 5) C
导体材料	退火铜
绝缘	PVC/Nylon
绝缘色	Black w. number + yellow/green
加蔽线	镀锡铜
屏蔽	≥85% tinned copper braid coverage
外护套	特殊聚氯乙烯
护套颜色	黑

尺寸特性

导线截面	2.5 mm ²
------	---------------------



操作温度
-5 ... 90 ° C



阻燃 – 火焰
UL 1581 SEC. 1160 AND CSA FT4 是



耐油
是

尺寸特性

芯线数	5
外径	11.2 mm
铜含量	166 kg/km
近似重量	246 kg/km

电气特性

Rated Voltage U ₀ /U	600 V
测试电压	2000 V

使用特性

应用类型	固定安装
操作温度范围	-5 ... 90 ° C
最小弯曲半径 – 静态 (XD)	20
阻燃 – 火焰	UL 1581 SEC. 1160 AND CSA FT4
耐油	是



操作温度
-5 ... 90 ° C



阻燃 – 火焰
UL 1581 SEC. 1160 AND CSA FT4



耐油
是