



Reference: 10554451
Country Ref.: B1250256409
EAN 13: 8054803096083

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

UL-listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

UL MTW UL1063

UL TC-ER 90° C 600V UL1277

UL WTTC 90° C 1000V UL2277

UL DP-1

UL AWM 600V UL758

C(UL) C1C/TC

CHARACTERISTICS

结构特性

| | |
|------|--------------------------------|
| 结构类型 | 25G2, 5 |
| 导体材料 | 退火铜 |
| 绝缘 | — |
| 绝缘色 | Black w. number + yellow/green |
| 外护套 | 特殊聚氯乙烯 |
| 护套颜色 | 黑 |

尺寸特性

| | |
|------|---------------------|
| 导线截面 | 2.5 mm ² |
| 芯线数 | 25 |



操作温度
-5 ... 90 ° C



阻燃 – 火焰
UL 1581 SEC. 1160 AND CSA FT4 是



耐油
是

尺寸特性

| | |
|------|-----------|
| 外径 | 22.7 mm |
| 铜含量 | 600 kg/km |
| 近似重量 | 992 kg/km |

电气特性

| | |
|---------------------------------|--------|
| Rated Voltage U ₀ /U | 600 V |
| 测试电压 | 2000 V |

使用特性

| | |
|------------------|-------------------------------|
| 应用类型 | 固定安装 |
| 操作温度范围 | -5 ... 90 °C |
| 最小弯曲半径 – 静态 (XD) | 15 |
| 阻燃 – 火焰 | UL 1581 SEC. 1160 AND CSA FT4 |
| 耐油 | 是 |

操作温度
-5 ... 90 °C阻燃 – 火焰
UL 1581 SEC. 1160 AND CSA FT4耐油
是