



Reference: 10554587
Country Ref.: B1100186409
EAN 13: 8054803093365

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

UL - listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC - ER and MTW approved, UL Listed

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

UL MTW UL1063

UL TC - ER 90 ° C 600V UL1277

UL WTTC 90 ° C 1000V UL2277

UL DP - 1

UL AWM 600V UL758

C(UL) CIC/TC

CHARACTERISTICS

18G1

Insulation colour

Black w. number + yellow/green

Sheath colour

1 mm²

18

14.6 mm

Copper content

173 kg/km

()

372 kg/km



Operating temp.
-5 ... 90 ° C



UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes

Rated Voltage U ₀ /U	600 V
	2000 V
Field of application	Fixed installations
操作度范	- 5 ... 90 ° C
Minimum bending radius, static (XD)	15
	UL 1581 SEC. 1160 AND CSA FT4
Oil resistance	Yes



Operating temp.
- 5 ... 90 ° C



UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes