



Country Ref.: C1250256409

CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

UL-listed tray cables (TC-ER) cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, shielded, oil resistant, flame retardant, TC-ER and MTW approved, UL Listed. suitable for American and Canadian market

STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- cable tray in factories in industry
- Industrial sector
- wind turbine application

Approvals:

UL MTW UL1063

UL TC-ER 90°C 600V UL1277

UL WTTC 90°C 1000V UL2277

UL DP-1

UL AWM 600V

C(UL) CIC/TC

CHARACTERISTICS

Construction characteristics

| | |
|--------------------|-----------------------------------|
| Construction type | (25G2,5)C |
| Conductor material | Annealed copper |
| Insulation | PVC/Nylon |
| Insulation colour | Black w. number + yellow/green |
| Drain wire | Tinned copper |
| Shielding | ≥85% tinned copper braid coverage |
| Outer sheath | Special PVC compound |
| Sheath colour | Black |

Dimensional characteristics

| | |
|-------------------------|---------------------|
| Conductor cross-section | 2.5 mm ² |
| Number of cores | 25 |



Operating temp.
-5 ... 90 °C



Flame retardant
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes

Dimensional characteristics

| | |
|--------------------|------------|
| Outer Diameter | 23.8 mm |
| Copper content | 635 kg/km |
| Approximate weight | 1062 kg/km |

Electrical characteristics

| | |
|---------------------------------|--------|
| Rated Voltage U ₀ /U | 600 V |
| Test voltage | 2000 V |

Usage characteristics

| | |
|-------------------------------------|-------------------------------|
| Field of application | Fixed installations |
| Operating temperature, range | -5 ... 90 °C |
| Minimum bending radius, static (XD) | 20 |
| Flame retardant | UL 1581 SEC. 1160 AND CSA FT4 |
| Oil resistance | Yes |



Operating temp.
-5 ... 90 °C



Flame retardant
UL 1581 SEC. 1160 AND CSA FT4



Oil resistance
Yes