



Reference: 10101846
EAN 13: 3427580238741

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

- Instrumentation cables 300 V
- Individual & Overall Screen (IOS)
- **Low smoke, low halogen (LSLH)**
- **Oil resistant**

STANDARDS

Product IEC 60228

Test IEC 60332-3-22 Cat.A; IEC 60754; IEC 61034

APPLICATIONS

These cables are intended for transmission of analogue and digital signals. They allow transmission over long distances at high pulse rates. The individual screening of each pair limits the consequences of crosstalk. These cables are used in industrial installations such as refineries, chemical plants etc...

Design

Conductor:

Stranded bare copper (class 2)

Insulation:

Polyethylene (PE)

Individual screen:

Tinned copper drain wire

Aluminium/polyester tape

Overall screen:

Tinned copper drain wire

Aluminium/polyester tape

Outer sheath:

Polyvinyl chloride (PVC)

Special low smoke, low halogen (LSLH)

Colour: black or blue

Fire retardant: IEC 60332-3-22(A), limiting oxygen index > 30 as par ASTM D 2863

Low smoke: IEC 61034-2, transmittance > 40 %

Low halogen: IEC 60754-1 HCL < 6 %

Core identification

Pair: Black/white
 For multipair: White core printed with pair number



Conductor flexibility
 Stranded class 2



Fire retardant
 EN IEC 60332-3-22 (cat. A)



Oil resistance
 IEC 60754-1



Smoke density
 Low



Operating temp.
 -20 ... 60 °C



Max. conductor temp. in service
 70 °C

Marking

GORSE YYYY RE - 2Y(St)Y - fl PiMF LSLH 300V Nber of pairs & cross-section IEC 60332-3-22(A) + metric marking

Désignation

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxéo is indicative only and shall not be binding. The drawings are constituting a representation on the part of Lynxéo.

RE: Instrumentation cables
 2Y: Polyethylene insulation
 (St): Collective screen

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Conductor flexibility	Stranded class 2
Insulation	PE
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Outer sheath	PVC
Sheath colour	Blue

Dimensional characteristics

Conductor cross-section	0.75 mm ²
Number of pairs	2
Minimum outer diameter	9.6 mm
Maximum outer diameter	10.6 mm
Approximate weight	135 kg/km

Electrical characteristics

Operating voltage	300 V
-------------------	-------

Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	ASTM D 1047
Smoke density	Low
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	70 °C
Standard	EN

ELECTRICAL CHARACTERISTICS

Electrical data AT 20°C

Cables (mm ²)	Conductor Resistance max. (Ohm / km)	Insulation Resistance min. (Mohm.km)	Mutual Capacitance at 800 Hz maximum (nF / km)	L/R ratio max (µH / ohm)	Test Voltage (core/core) (V)
0.5	36.7	5 000	115	25	2 000
0.75	24.9	5 000	115	25	2 000
1.34	14.2	5 000	115	40	2 000



Conductor flexibility
Stranded class 2



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
ASTM D 1047



Smoke density
Low



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
70 °C

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations



Conductor flexibility
Stranded class 2



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
ASTM D 1047



Smoke density
Low



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
70 °C