



Reference: 10108667
EAN 13: 3427580168727

CONTACT

Market information
 industryprojects.business@lynxéo
 ogroup.com

- 0.6/1 kV Power and control cables
- Armoured with galvanized steel wires (SWA) or aluminium wires (AWA)
- **Oil resistant**

STANDARDS

Product IEC 60228; IEC 60502-1

Test IEC 60332-3-22 Cat.A

APPLICATIONS

These power and control cables are used for electricity supply in **low voltage installation system**. They are well adapted to underground use in industrial applications where **chemical and mechanical protections are needed** (refinery areas, chemical plants...).

Design

Conductor:

Solid plain copper : 1.5 to 4 mm²

Stranded plain copper : 1.5 to 630 mm²

Insulation:

Cross-linked polyethylene (XLPE)

Bedding(optional):

Inner sheath acting as a filler with practically zero thickness or assembling polyester tape

Inner covering (inner sheath):

Polyvinyl chloride (PVC) Colour :black

Armour:

Galvanized steel wires (SWA) or aluminium wires (AWA) for 1 core cable

Outer sheath:

Polyvinyl chloride (PVC). Colour: black. Other colour on request.

Core identification

1 core: black

2x to 5G cores: according to HD 308 S2

Above 5 cores: black core printed with white number.

Marking

NEXANS 279 XLPE/PVC/AWA or SWA/PVC 0.6/1 kV Nber of cores and cross section Cu IEC 60332-3-22(A) MM YYYY manufacturing number + meter marking



Rated Voltage U₀/U (Um)
 0,6/1 kV



Mechanical resistance to impacts
 Good



Fire retardant
 EN IEC 60332-3-22 (cat A)



Oil resistance
 Yes



Max. conductor temp.in service
 90 °C



Operating temp.
 -20 ... 60 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	XLPE (Cross-linked Polyethylene)
Inner sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes
With Green/Yellow core	No

Dimensional characteristics

Number of cores	4
Conductor cross-section	16 mm ²
Conductor diameter	4.85 mm
Diameter over insulation	6.25 mm
Diameter over inner sheath	17.4 mm
Diameter over armour	20.6 mm
Minimum outer diameter	23.47 mm
Maximum outer diameter	25.9 mm
Approximate weight	1568.84 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (Um)	0,6/1 kV
--------------------------------------	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	Yes
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3 -24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

- 1 core: 10 x outer diameter
- Multicores: 8 x outer diameter
- To be doubled during laying operations



Rated Voltage U₀/U (Um)
0,6/1 kV



Mechanical resistance to impacts
Good



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Max. conductor temp. in service
90 °C



Operating temp.
-20 ... 60 °C

Cables with reduced neutral on request



Rated Voltage U₀/U (U_m)
0,6/1 kV



Mechanical resistance to impacts
Good



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Max. conductor temp. in service
90 °C



Operating temp.
-20 ... 60 °C