



**Reference:** 10134809  
**EAN 13:** 3427580318504

#### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

#### STANDARDS

**Test** IEC 60332-3-22 Cat.A

#### APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control** .They are well adapted to **underground use in industrial application where chemical and mechanical protections are needed (refinery areas, chemical plan...)** .

#### Design

##### Conductor:

Stranded bare copper class 2

##### Insulation:

Cross-linked polyethylene (XLPE)

##### Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

##### Inner sheath:

Polyvinyl chloride (PVC).

Colour : black

##### Armour:

Galvanized steel wires (SWA)

##### Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

#### Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number



Rated Voltage Uo/U (Um)  
 170/300V



Mechanical resistance to impacts  
 Good



Fire retardant  
 EN IEC 60332-3-22 Cat.A



Oil resistance



Electro magnetic interference resistance  
 Yes



Operating temp.  
 -20 to 90 °C



Max. conductor temp.in service  
 90 °C

#### Marking

EN IEC 60332-3-22 Cat.A  
 NEXANS 279 XLPE/OA.SCR/PVC/SWA/PVC 170/300V nber of pairs & cross-section  
 Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

#### Standards

EN 50288-7 (design guidelines)  
 All drawings, design guidelines and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxéo is indicative only and shall not be binding on Lynxéo or be treated as constituting a representation on the part of Lynxéo.

### CHARACTERISTICS

#### Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	XLPE (Cross-linked Polyethylene)
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

#### Dimensional characteristics

Number of pairs	20
Conductor cross-section	1.5 mm <sup>2</sup>
Conductor diameter	1.5 mm
Diameter over insulation	2.16 mm
Diameter over inner sheath	22.7 mm
Diameter over armour	25.2 mm
Minimum outer diameter	27.7 mm
Maximum outer diameter	30.6 mm
Approximate weight	1500 kg/km

#### Electrical characteristics

Rated Voltage U <sub>0</sub> /U (Um)	170/300V
--------------------------------------	----------

#### Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

#### Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	Yes
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN

### SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:



Rated Voltage U<sub>0</sub>/U (Um)  
170/300V



Mechanical resistance to impacts  
Good



Fire retardant  
EN IEC 60332-3-22 (cat A)



Oil resistance  
Yes



Electro magnetic interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in service  
90 °C

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U<sub>0</sub>/U  
(Um)  
170/300V



Mechanical resistance  
to impacts  
Good



Fire retardant  
EN IEC 60332-3-22  
(cat A)



Oil resistance  
Yes



Electro magnetic  
interference resistance  
Yes



Operating temp.  
-20 ... 60 °C



Max. conductor temp.in  
service  
90 °C