



**Reference:** 10167494  
**EAN 13:** 3427650093348

### CONTACT

Market information  
 industryprojects.business@lynxéogroup.com

### INSTRUMENTATION, CONTROL AND COMMUNICATION cables

### STANDARDS

**Product** IEC 60228

**Installation** IEC 60092-350; IEC 60092-360; IEC 60092-376

**Test a;** IEC 60332-1; IEC 60332-3-22; IEC 60754-1; IEC 61034

### APPLICATION

TX® (C) 150/250 V overall screened twisted pair cables are used for telecommunication and instrumentation purposes. These cables provide a medium protection against external electromagnetic disturbances. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

### Design

- 1. Conductor**  
Stranded bare copper class 2
- 2. Insulation**  
XLPE (cross-linked polyethylene)
- 3. Collective screen**  
Alu/polyester tape with a tinned copper drain wire
- 4. Outer sheath**  
Polyolefin SHF1  
Colour : grey

#### Example of marking

LYNXEO 279 TX(C) Nbr of pairs/triads & cross-section 150/250V 90C IEC 60092-376 IEC 60332-3-22 Cat. A WW YYYY \*CE\* Manufacturing n°+ metric marking

#### Core Identification

Pair: white / blue with printed with pair number

Triad: white / blue / red with printed with triad number



Conductor flexibility  
Stranded class 2



Halogen free  
IEC 60754-1



Rated Voltage U<sub>0</sub>/U  
(Um)  
150 / 250 (300) V



Fire retardant  
EN IEC 60332-3-22  
(cat A)



Flame retardant  
IEC 60332-1



Smoke density  
IEC 61034



Gases corrosivity  
IEC 60754-2



Electro magnetic  
interference  
resistance  
Yes

**CHARACTERISTICS****Construction characteristics**

Conductor material	Bare copper
Conductor flexibility	Stranded class 2
Insulation	XLPE (Cross-linked Polyethylene)
Overall screen	Aluminium/polyester tape
Drain wire	Tinned copper
Outer sheath	Polyolefin
Sheath colour	Grey
Halogen free	IEC 60754-1

**Dimensional characteristics**

Number of pairs	2
Number of triples	-
Conductor cross-section	0.75 mm <sup>2</sup>
Nominal outer diameter	7.42 mm
Minimum outer diameter	6.9 mm
Maximum outer diameter	7.9 mm
Approximate weight	71 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	150 / 250 (300) V
Max. DC resistance of the conductor at 20°C	52 Ohm/km

**Usage characteristics**

Fire retardant	EN IEC 60332-3-22 (cat A)
Flame retardant	IEC 60332-1
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
Electro magnetic interference resistance	Yes
Operating temperature, range	-30 ... 80 °C
Max. conductor temperature in service	90 °C

**OTHER CHARACTERISTICS****Test Voltage**

AC between cores of the same unit..... 1.5 kV

**Minimum bending radius for fixed installations**

- cable diameter ≤ 25 mm..... 4 x outer diameter
- cable diameter > 25 mm..... 6 x outer diameter