



Reference: 10168681
EAN 13: 3427580414299

CONTACT

Market information
industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Individual & Overall Screen (IOS)
- Oil resistant

STANDARDS

Test IEC 60332-3-22 Cat.A

APPLICATIONS

These Instrumentation and communication are used to **transmit analogue or digital signals in measurement and process control** They are well adapted **to underground use in industrial applications where chemical and mechanical protections are needed (refinery areas, chemical plant...)**. The individual screening of each pair limits the consequence of crosstalk.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Polyester tape

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Inner sheath:

Polyvinyl chloride (PVC)

Armour:

Galvanized steel wires (SWA)

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request

Fire retardant
EN IEC 60332-3-22
Yes

Oil resistance
Yes



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in service
90 °C



Rated Voltage U₀/U
(Um)
170/300V



Mechanical resistance to impacts
Good

Core identification

Pair: white - black
White core printed with pair number

All the marking designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxéo is indicative only and shall not be binding on Lynxéo or be treated as constituting a representation on the part of Lynxéo.
NEXANS 279 XLPE/IND.+OA.SCR/PVC/SWA/PVC 170/300V Nber of pairs & cross-section
Cu IEC 60332-3-22(A) MM YYY Y Manufacturing number + metric marking

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	XLPE (Cross-linked Polyethylene)
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

Dimensional characteristics

Number of pairs	10
Conductor cross-section	1 mm ²
Conductor diameter	1.28 mm
Diameter over insulation	1.76 mm
Diameter over inner sheath	15.4 mm
Diameter over armour	17.2 mm
Minimum outer diameter	19.6 mm
Maximum outer diameter	21.6 mm
Approximate weight	750 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (Um)	170/300V
--------------------------------------	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	Yes
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:



Rated Voltage U₀/U (Um)
170/300V



Mechanical resistance to impacts
Good



Fire retardant
EN IEC 60332-3-22
(cat A)



Oil resistance
Yes



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
90 °C

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U₀/U
(Um)
170/300V



Mechanical resistance
to impacts
Good



Fire retardant
**EN IEC 60332-3-22
(cat A)**



Oil resistance
Yes



Electro magnetic
interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in
service
90 °C