



**Reference:** 10170094  
**EAN 13:** 3427650094055

### CONTACT

Market information  
 industryprojects.business@lynx<sup>eo</sup>.group.com

## INSTRUMENTATION, CONTROL and COMMUNICATION Cables

### STANDARDS

**Product** IEC 60092-375

**Installation** IEC 60092-3

**Test** a; IEC 60332-3 Cat.A; IEC 60754-1; IEC 61034

**International** IEC 60298

### APPLICATION

TCX<sup>®</sup> (I) 150/250 V armoured individually screened twisted pair cables are used for telecommunication and instrumentation purposes. These cables provide strong protection against cross-talk in both low and high frequency runs, making them suitable for highly polluted electromagnetic surroundings. TCX<sup>®</sup>(I) cables are also selected where enhanced mechanical protection is required. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

### Design

- 1. Conductor**  
Stranded bare copper class 2
- 2. Insulation**  
XLPE (cross-linked polyethylene)
- 3. Individual screen**  
Alu/polyester tape with a tinned copper drain wire
- 4. Assembling**  
Polyester tape
- 5. Armour**  
Bare copper braid
- 6. Outer sheath**  
Polyolefin SHF1  
Colour : grey

Example of marking:

LYNXEO 279 TCX (I) Nber of pairs/triads & cross section 150/250V 90C IEC 60092-376 IEC 60332-3-22 Cat. A WW YYYY \*CE\* Manufacturing n° + metric marking

Core identification

Pair: white / blue with printed pair number

Triad: white / blue / red with printed triad number



Halogen free  
IEC 60754-1



Conductor flexibility  
Stranded class 2



Rated Voltage Uo/U  
(Um)  
150 / 250 (300) V



Fire retardant  
EN IEC 60332-3-22  
(cat A)



Flame retardant  
IEC 60332-1



Smoke density  
IEC 61034



Gases corrosivity  
IEC 60754-2



Electro magnetic  
interference  
resistance  
Yes

**CHARACTERISTICS****Construction characteristics**

Halogen free	IEC 60754-1
Conductor material	Bare copper
Conductor flexibility	Stranded class 2
Insulation	XLPE (Cross-linked Polyethylene)
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Inner covering	Polyester tape(s)
Armour type	Bare copper braid
Outer sheath	Polyolefin
Sheath colour	Grey
Drain wire	-
Number of conductors	-

**Dimensional characteristics**

Number of pairs	4
Number of triples	-
Conductor cross-section	0.75 mm <sup>2</sup>
Nominal outer diameter	12.7 mm
Minimum outer diameter	11.8 mm
Maximum outer diameter	13.6 mm
Approximate weight	216 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	150 / 250 (300) V
Max. DC resistance of the conductor at 20°C	52 Ohm/km

**Usage characteristics**

Fire retardant	EN IEC 60332-3-22 (cat A)
Flame retardant	IEC 60332-1
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
Electro magnetic interference resistance	Yes
Operating temperature, range	-30 ... 80 °C
Max. conductor temperature in service	90 °C

**OTHER CHARACTERISTICS****Test Voltage**

Between cores of the same unit..... 1,5 kV AC

**Minimum bending radius for fixed installations TCX® (I)**..... 6 x outer diameter