



**Reference:** 10170128  
**EAN 13:** 3427650094192

### CONTACT

Market information  
 industryprojects.business@lynxéo  
 group.com

## INSTRUMENTATION, CONTROL and COMMUNICATION cables

### STANDARDS

**Product** IEC 60092-375

**Installation** IEC 60092-3

**Test** a; IEC 60332-3 Cat.A; IEC 60754-1; IEC 61034

**International** IEC 60298

### APPLICATION

TCX® (C) 150/250 V armoured twisted pair cables are used for telecommunication and instrumentation purposes. These cables show a low transfer impedance in low frequency and an effective screening in high frequency, making them very suitable for polluted electromagnetic surroundings. TCX® (C) cables are also selected where enhanced mechanical protection is required. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

### Design

- 1. Conductor**  
Stranded bare copper class 2
- 2. Insulation**  
XLPE(cross-linked polyethylene)
- 3. Assembling**  
Polyester tape
- 4. Armour**  
Bare copper braid
- 5. Outer sheath**  
Polyolefin SHF1  
Colour : grey

Example of marking:

LYNXEO 279 TCX (C) Nbr of pairs/triads & cross-section 150/250V 90C IEC 60092-376  
 IEC 60332-3-22 Cat.A WW YYYY \*CE\* Manufacturing n°+ metric marking

Core identification

Pair: white / blue with printed pair number

Triad: white / blue / red with printed triad number



Halogen free  
 IEC 60754-1



Conductor flexibility  
 Stranded class 2



Rated Voltage U<sub>0</sub>/U  
 (Um)  
 150 / 250 (300) V



Fire retardant  
 EN IEC 60332-3-22  
 (cat A)



Flame retardant  
 IEC 60332-1



Smoke density  
 IEC 61034



Gases corrosivity  
 IEC 60754-2



Electro magnetic  
 interference  
 resistance  
 Yes

**CHARACTERISTICS****Construction characteristics**

Halogen free	IEC 60754-1
Conductor material	Bare copper
Conductor flexibility	Stranded class 2
Insulation	XLPE (Cross-linked Polyethylene)
Inner covering	Polyester tape(s)
Armour type	Bare copper braid
Outer sheath	Polyolefin
Sheath colour	Grey

**Dimensional characteristics**

Number of pairs	4
Number of triples	-
Conductor cross-section	1.5 mm <sup>2</sup>
Nominal outer diameter	15.3 mm
Minimum outer diameter	14.2 mm
Maximum outer diameter	16.4 mm
Approximate weight	323 kg/km

**Electrical characteristics**

Max. DC resistance of the conductor at 20°C	25.6 Ohm/km
Rated Voltage U <sub>0</sub> /U (Um)	150 / 250 (300) V

**Usage characteristics**

Fire retardant	EN IEC 60332-3-22 (cat A)
Flame retardant	IEC 60332-1
Smoke density	IEC 61034
Gases corrosivity	IEC 60754-2
Electro magnetic interference resistance	Yes
Operating temperature, range	-30 ... 80 °C
Max. conductor temperature in service	90 °C

**OTHER CHARACTERISTICS****Test Voltage**

Between cores of the same unit..... 1,5 kV AC

**Minimum bending radius for fixed installations**..... 6 x outer diameter