



Reference: 10176323
Country Ref.: 01272421
EAN 13: 3427580464881

CONTACT

Market information
 industryprojects.business@lynx^{eo}.com
 ogroup.com

Control cables CST 74C068 for nuclear power plants, 500V halogen-free. These cables, installed outside the containment area (K3), are unarmed and designed with copper braid shield.

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross linked

Assembling:

- Polyester tape (optional)

Overall screen:

- Copper wire braid (CWB) R ≥ 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)

- Colour: Grey

Core identification

Black cores printed with white numbers

Optional: with Y/G core

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1; IEC 60754-2



Operating temp.
 -20 ... 60 °C



Smoke density
 EN/IEC 61034-2



Fire retardant
 NF C 32070 C1;
 IEC 60332-3-24
 (cat.B)



Electro magnetic
 interference
 resistance
 Yes



U.V resistance
 Yes



Life cycle 60years
 Yes



Max. conductor
 temp.in service
 90 °C

CHARACTERISTICS**Construction characteristics**

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

Dimensional characteristics

Conductor cross-section	1 mm ²
Number of cores	27
Conductor diameter	1.3 mm
Diameter over insulation	2.58 mm
Diameter over screen	16.5 mm
Minimum outer diameter	20.6 mm
Maximum outer diameter	23.8 mm
Approximate weight	765 kg/km

Electrical characteristics

Max. DC resistance of the conductor at 20°C	18.1 Ohm/km
Maximum DC resistance of the conductor at 90°C	23.000 Ohm/km
Reactance at 50 Hz	0.1 Ohm/km
Short Circuit Current 0,3 s Max	0.26 kA
Short Circuit Current 1 s Max	0.14 kA
Impedance at 50 Hz	18.1 Ohm
Voltage Drop	36.9 V/A.km
Calorific Power	7.3 MJ/m

Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	EN/IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Electro magnetic interference resistance	Yes
U.V resistance	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION**Minimum bending radius:**

10 x outer diameter
To be doubled during laying operations