



Reference: 10192908
EAN 13: 3427580555008

CONTACT

Market information
industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

STANDARDS

Test IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control where chemicals may be present.**

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number

Marking

NEXANS 279 XLPE/OA.SCR/PVC 170/300V Nber of pairs & cross-section Cu IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

Standards

EN 50288-7 (Design guide-lines)



Rated Voltage U₀/U (Um)
170/300V



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Electro magnetic interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	XLPE (Cross-linked Polyethylene)
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Outer sheath	PVC
Protection	no

Dimensional characteristics

Number of pairs	5
Conductor cross-section	0.5 mm ²
Diameter over insulation	1.38 mm
Approximate weight	130 kg/km
Conductor diameter	0.9 mm
Maximum outer diameter	11.4 mm
Minimum outer diameter	10.4 mm

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	170/300V
---	----------

Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	Yes
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U₀/U (U_m)
170/300V



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Electro magnetic interference
resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C