



Reference: 10194035
EAN 13: 3427580560170

CONTACT

Markets and Products Information
rollingstock.business@lynxgroup.com

- CST 74C068
- Quality insurance according to RCC - E
- Zero halogen (SH)
- Control cables 0.15/0.25 (0.3)kV
- Cables installed outside of the containment area (K3)
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332 - 3 - 23; IEC 60754 - 1; IEC 61034 - 2; NF C32 - 070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

DESIGN

Conductor: - Stranded plain copper (class 2)

Insulation: - Zero halogen (SH), cross-linked

Assembling: Polyester tape (optional)

Overall screen: - Copper wire braid (CWB) R 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.15/0.25 (0.3) kV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754 - 1; IEC
60754 - 2



Operating temp.
- 20 ... 60 °C



IEC 61034 - 2



Fire retardant
NF C 32070 C1;
IEC 60332 - 3 - 24
(cat.B)



Electro magnetic
interference
resistance
Yes



U.V resistance
Yes



Life cycle 60years
Yes



Max. conductor
temp. in service
90 °C

CHARACTERISTICS

	2	()
		Copper Braid
Halogen free		IEC 60754 - 1; IEC 60754 - 2
		0.44 mm ²
		12
		0.9 mm
Diameter over insulation		1.8 mm
Diameter over screen		8.8 mm
Minimum outer diameter		11.7 mm
Maximum outer diameter		13.5 mm
()		270 kg/km
20 ° C	DC	36 Ohm/km
Maximum DC resistance of the conductor at 90 ° C		45.900 Ohm/km
Reactance at 50 Hz		0.103 Ohm/km
Short Circuit Current 0,3 s Max		0.13 kA
Short Circuit Current 1 s Max		0.07 kA
Impedance at 50 Hz		36 Ohm
Voltage Drop		73.6 V/A.km
Calorific Power		2.5 MJ/m
操作度范		- 20 ... 60 ° C
		IEC 61034 - 2
Fire retardant		NF C 32070 C1; IEC 60332 - 3 - 24 (cat.B)
Electro magnetic interference resistance		Yes
U.V resistance		Yes
Life cycle 60years		Yes
Max. conductor temperature in service		90 ° C
Nuclear Classification		Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations