



Reference: 10195518
EAN 13: 3427580567544

CONTACT

Market information
 industryprojects.business@lynx^{eo}.com
 ogroup.com

- Instrumentation cables 300/500(600) V
- CST 74C068
- Zero halogen (SH)
- **Cables installed inside of the containment area (K1)**
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These instrumentation cables allow connection to a variety of measurement equipment. Many of them require anti-inductive screen (EMI).

CONSTRUCTION

Design

Conductor:

Flexible bare copper (class 5)

Insulation:

Cross-linked halogen free (SH)

Assembling tape (optional):

Inner sheath:

Low smoke, zero halogen (LSZH)

Overall screen:

Copper wire braid (CWB)

Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: white

Core identification

Black cores printed with white numbers



Halogen free
 IEC 60754-1



Rated Voltage Uo/U
 (Um)
 300/500 V



LYNXEO 279 Nber of pairs or triads & cross section
 0 3/0.5 (0.6) kV YYY Y Manufacturing number + metric marking
 Fire retardant NF C 32070 C1; IEC 60332-3-24 (cat. B)
 Smoke density EN/IEC 61034-2



Electro magnetic interference resistance
 Yes



LIFE TIME
 60
 Life Cycle 60years
 Yes



Radiation resistant
 Yes



LOCA
 Yes

Standard

IEC 60332-3-23(B)

Quality insurance according to BCC-F

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of LynxEO is indicative only and shall not be binding on LynxEO or be treated as constituting a representation on the part of LynxEO.

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Flexible, Classe 5
Insulation	Halogen-free
Inner sheath	Halogen free compound
Screen	Copper Braid
Outer sheath	Halogen free
Halogen free	IEC 60754-1

Dimensional characteristics

Conductor cross-section	1 mm ²
Conductor diameter	1.3 mm
Diameter over insulation	2.58 mm
Diameter over inner sheath	7.6 mm
Diameter over screen	8.45 mm
Minimum outer diameter	10.6 mm
Maximum outer diameter	12.1 mm
Approximate weight	223 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	300/500 V
---	-----------

Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Electro magnetic interference resistance	Yes
Life cycle 60years	Yes
Radiation resistant	Yes
Loss of coolant accident resistant	Yes
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C
Nuclear Classification	Class 1 E LOCA /K1

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

8 x outer diameter
To be doubled during laying operations

2 pair cables (QE) are assembled as a quad (1.3.2.4)



Halogen free
IEC 60754-1



Rated Voltage U_o/U (U_m)
300/500 V



Fire retardant
NF C 32070 C1;
IEC 60332-3-24
(cat.B)



Smoke density
EN/IEC 61034-2



Electro magnetic
interference
resistance
Yes



Life cycle 60years
Yes



Radiation resistant
Yes



LOCA
Yes

Marking

LYNXEO 279 Nber of pairs or triads & cross-section Cu EG CST 74 C 068 00 K1 SH 0.3/0.5 (0.6)
 kV YYYY Manufacturing number + metric marking



Halogen free
IEC 60754-1



Rated Voltage U₀/U_i
(Um)
300/500 V



Fire retardant
NF C 32070 C1;
IEC 60332-3-24
(cat.B)



Smoke density
EN/IEC 61034-2



Electro magnetic
interference
resistance
Yes



Life cycle 60years
Yes



Radiation resistant
Yes



LOCA
Yes