



**Reference:** 10203612  
**EAN 13:** 3427580598609

#### CONTACT

Market information  
 industryprojects.business@lynx<sup>eo</sup>  
 ogroup.com

Control cables CST 74C068 for nuclear power plants, 500V halogen-free. These cables, installed outside the containment area (K3), are unarmed and designed with copper braid shield.

#### STANDARDS

**Product** IEC 60228

**Test** IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

#### APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

#### CONSTRUCTION

##### Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

##### Insulation:

- Zero halogen (SH), cross linked

##### Assembling:

- Polyester tape (optional)

##### Overall screen:

- Copper wire braid (CWB) R ≥ 80%

##### Outer sheath:

- Low smoke, zero halogen (LSZH)

- Colour: Grey

#### Core identification

Black cores printed with white numbers

Optional: with Y/G core

#### Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free  
 IEC 60754-1; IEC 60754-2



Operating temp.  
 -20 ... 60 °C



Smoke density  
 EN/IEC 61034-2



Fire retardant  
 NF C 32070 C1;  
 IEC 60332-3-24  
 (cat.B)



Electro magnetic  
 interference  
 resistance  
 Yes



U.V resistance  
 Yes



Life cycle 60years  
 Yes



Max.conductor  
 temp.in service  
 90 °C

## CHARACTERISTICS

### Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

### Dimensional characteristics

Conductor cross-section	6 mm <sup>2</sup>
Number of cores	4
Conductor diameter	2.95 mm
Diameter over insulation	4.4 mm
Diameter over screen	11.7 mm
Minimum outer diameter	14.2 mm
Maximum outer diameter	16.2 mm
Approximate weight	481 kg/km

### Electrical characteristics

Max. DC resistance of the conductor at 20°C	3.08 Ohm/km
Maximum DC resistance of the conductor at 90°C	3.920 Ohm/km
Reactance at 50 Hz	0.083 Ohm/km
Short Circuit Current 0,3 s Max	1.6 kA
Short Circuit Current 1 s Max	0.86 kA
Impedance at 50 Hz	3.08 Ohm
Voltage Drop	6.4 V/A.km
Calorific Power	3.4 MJ/m

### Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	EN/IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Electro magnetic interference resistance	Yes
U.V resistance	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

## SELLING AND DELIVERY INFORMATION

### Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations