



**Reference:** 10211786  
**Country Ref.:** 2PK595

**CONTACT**

Markets and Products Information  
 rollingstock.business@lynxeogroup.com

**COMMUNICATION CABLES**

FLAMEX® WTB cables are intended for Train Communication Network to connect the different vehicles. They are designed to improve the protection against electrical disturbances, electromagnetic noises

**STANDARDS**

**Product** EN 45545-2 (HL3); EN 50264-1

**DESIGN**

**1. Conductor**

Stranded tinned copper

**2. Insulation**

Foam polyethylene

**3. Screen**

Tinned copper braid  
 Separator tape

**4. Outer sheath**

Cross-linked material EM 104 or EM 101 acc. EN 50264-1  
 Oil, diesel, ozone and UV resistant  
 Colour: black or turquoise

Example of marking: FLAMEX 239 - EDE 2PF578 - 2x0.75 mm² 120 OHMS - week/year - batch number

**GUIDE TO USE**

- Bending radius:
  - Static use: 5 x outer cable diameter
  - For installation and occasional movements: 10 x outer cable diameter



Conductor flexibility  
 Flexible stranded



Halogen free  
 EN 60754-1 & EN 60684-2



Flame retardant  
 EN 60332-1-2



Fire retardant  
 EN IEC 60332-3-25 (cat D)



Smoke density  
 EN/IEC 61034-2



Gases toxicity  
 EN 50305-9.2



Minimum operating temperature  
 -25 °C



Electro magnetic interference resistance  
 Yes

**CHARACTERISTICS****Construction characteristics**

Type of cable	WTB
Conductor material	Tin plated copper
Conductor flexibility	Flexible stranded
Construction type	2 x 0.75 <sup>2</sup>
Sheath colour	Turquoise
Core identification	Black, White
Outer sheath	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2

**Dimensional characteristics**

Nominal outer diameter	8.5 mm
Approximate weight	92 kg/km

**Usage characteristics**

Flame retardant	EN 60332-1-2
Fire retardant	EN IEC 60332-3-25 (cat D)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Minimum operating temperature	-25 °C
Electro magnetic interference resistance	Yes
Chemical resistance	Good