



Reference: 10213052
EAN 13: 3427580629686

CONTACT

Market information
 industryprojects.business@lynx^{eo}.com
 ogroup.com

- CST 74C068
- Quality insurance according to RCC-E
- Zero halogen (SH)
- Control cables 0.3/0.5 (0.6) kV
- **Cables installed inside of the containment area (K2)**
- Overall screened (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross-linked

Assembling:

- Polyester tape (optional)

Inner sheath:

- Low smoke, zero halogen (LSZH)
- Colour: grey

Screen:

- Copper wire braid (CWB) R ≥ 80 %

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: grey

Core identification

Black cores printed with white numbers
 Optional: with G/Y core.

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K2 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1; IEC 60754-2



Operating temp.
 -20 ... 60 °C



Smoke density
 IEC 61034-2



Fire retardant
 NF C 32070 C1;
 IEC 60332-3-24 (cat.B)



Electro magnetic interference resistance
 Yes



U.V resistance
 Yes



Life cycle 60years
 Yes



Radiation resistant
 Yes

CHARACTERISTICS**Construction characteristics**

| | |
|--------------------|--------------------------|
| Conductor material | Plain copper |
| Type of conductor | Stranded, class 2 |
| Insulation | Halogen-free |
| Inner sheath | - |
| Screen | Bare copper braid |
| Outer sheath | LSZH |
| Halogen free | IEC 60754-1; IEC 60754-2 |

Dimensional characteristics

| | |
|----------------------------|---------------------|
| Conductor cross-section | 0.5 mm ² |
| Number of cores | 37 |
| Conductor diameter | 0.9 mm |
| Diameter over insulation | 2.2 mm |
| Diameter over inner sheath | 17.2 mm |
| Diameter over screen | 18.5 mm |
| Minimum outer diameter | 20.5 mm |
| Maximum outer diameter | 24.1 mm |
| Approximate weight | 830 kg/km |

Electrical characteristics

| | |
|--|---------------|
| Max. DC resistance of the conductor at 20°C | 36 Ohm/km |
| Maximum DC resistance of the conductor at 90°C | 45.900 Ohm/km |
| Reactance at 50 Hz | 0.112 Ohm/km |
| Short Circuit Current 0,3 s Max | 0.13 kA |
| Short Circuit Current 1 s Max | 0.07 kA |
| Impedance at 50 Hz | 36 Ohm |
| Voltage Drop | 73.6 V/A.km |
| Calorific Power | 5.8 MJ/m |

Usage characteristics

| | |
|--|---------------------------------------|
| Operating temperature, range | -20 ... 60 °C |
| Smoke density | IEC 61034-2 |
| Fire retardant | NF C 32070 C1; IEC 60332-3-24 (cat.B) |
| Electro magnetic interference resistance | Yes |
| U.V resistance | Yes |
| Life cycle 60years | Yes |
| Radiation resistant | Yes |
| Max. conductor temperature in service | 90 °C |
| Nuclear Classification | K2 |

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K2 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking